



# Quadruple Center Adjustable Polarizing Light Microscope A15.2603 WF10x / 18mm Eyepiece

### **Basic Information**

Place of Origin: China

• Brand Name: CNOEC, OPTO-EDU

Certification: CE, Rohs
Model Number: A15.2603
Minimum Order Quantity: 1 pc
Price: Negotiation

Packaging Details: Carton Packing, For Export Transportation

• Delivery Time: 5~20 Days

Payment Terms: T/T, West Union, Paypal

Supply Ability: 5000 pcs/ Month



## **Product Specification**

• Head: Seidentopf Head, Inclined 30°, Rotatable

360°, Interpupillary Distance 48-75mm, Left Eyepiece Tube Diopter Adjustable +/-5°, Trinocular Head Light Split 20:80.

• Eyepiece: WF10x/18mm, 1 Pc WF10x/18mm, With

Micrometer 0.1mm Div., 1 Pc

Nosepiece: Quadruple, Center Adjustable

• Objective: 4x, 10x, 20x, 40x

• Stage: Round Stage, Rotatable 360°, Center

Adjustable, Division 1°, Vernier Division 6'

• Condenser: Abbe N.A.1.25, With Iris Diaphragm, Non

Stress

• Focusing: Coaxial Coarse And Fine Focusing Knob,

Coarse Focusing Range 26mm

• Illumination: Transmit 6V20W Halogen Lamp

Power: 110V~240V Wide Range Voltage Product

Display

Highlight: atudant compound microscope



#### OPTO-EDU A15.2603-B 400X Trinocular Illumination Polarizing Microscope

A15.2603 Polarizing Microscope, with full polarizing function and high quality performance, is the best tools for school and student use.

- --Infinity achromatic correction optical system, infinity without stress flat field objective.
  - --Polarizer unit built-in condenser, with scale, rotatable 360°, can be locked.
- --Analyzer unit insert to polarizing media, rotatable 0-90°, can be moved out of optical path.
  - --Optical compensator: λ slip (first class red), 1/4λ slip.

A15.2603 Polarizing Microscope, with full polarizing function and high quality performance, is the best tools for school and student use.

It is a professional polarizing microscope, also named mineralogical microscope, with advanced multifunction, is necessary for researching double refraction sample. It can observe mineral crystal figure, color and interference color and also identify its optical performance. It is a good microscope used in geology, petroleum, coal, Chemical fiber, medical treatment, mineral, drug, criminal investigation fields and physic inspection. It is also widely used in academic demonstration and research.

Items	A15.2603 Transmit Polarizing Microscope Specification	-A	-В	Cata. No.
lland	Seidentopf Binocular Head Inclined 30°,Rotatable 360°, Interpupilary Distance 48- 75mm	•	0	A53.2621-B
Head	Seidentopf Trinocular Head Inclined 30°,Rotatable 360°, Interpupilary Distance 48- 75mm, , Light Split Fixed P20:E80	0	•	A53.2621-T
Eyepiece	WF10x/18mm, High Eyepoint,	•	•	A51.2602- 1018
Eyepiece	WF10x/18mm, With Micrometer X-0.1mm*180 Div / Y-Single Line, Diopter Adjustable	•	•	A51.2605- 1018D
Nosepiece	Quadruple, Backward	•	•	A54.2610-N08
	PLAN 4X/0.10, W.D.=12.1mm	•	•	A5P.2630-4
	PLAN 10X/0.25,W.D.=4.64mm	•	•	A5P.2630-10
Non-Stress	PLAN 20X/0.40(S),W.D.=2.41mm	•	•	A5P.2630-20
Infinity Plan Objective	PLAN 40X/0.66(S),W.D.=0.65mm	•	•	A5P.2630-40
Objective	PLAN 60X/0.80(S),W.D.=0.33mm	0	0	A5P.2630-60
	PLAN 100X/1.25(S,Oil),W.D.=0.12mm	0	0	A5P.2630-100
Working Stage	Round Stage Diameter Φ142mm, Rotatable 360°, Division 1', Vernier Division 6', Can Be Locked, Center Adjustable	•	•	A54.2602-S03
	iviicroscope, ivioving hange 40x40mm	0	0	A5P.2616
	Attachable Mechanical Stage For Polaring Microscope, Moving Range 30x45mm, Lecia Type, Avoid Hitting Objective Lens	0	0	A5P.2616-LK
Condenser	Non-Stress Abbe N.A.1.25, Iris Diaphragm, Center Adjustable With Polarizer Lens In Bottom	•	•	A56.2614-P6
	Analyzer Media Unit, Between Head And Body, Analyzer 0~90° Adjustable, With Betrand Lens Built-in, Can Be Moved Out Of Optical Path For Single Polarizing Observe	•	•	A5P.2621-S
Polarizing Unit	Compensator Slide, 3 Holes, With λ Slip (First Class Red) + 1/4λ Slip.	•	•	A5P.2613-22a
	Quartz Wedge Slide (I-IV Class)	•	•	A5P.2615-17
	Polarizer Lens, Bulit-in Bottom Part Of Condenser Can Be Moved Out Of Optical Path	•	A5P.2610-S	
- ·	12V 20W Halogen Lamp, Wide Voltage: 100V- 240V	•	•	A56.2613- 20W
	6V/30W Halogen Lamp	0	0	A56.2613- 30W
	3W LED Lamp	0	0	A56.2651-3W
	Dia.45mm, Blue (Built in)	•	•	A56.2616-45B
Filter	Dia.45mm, Green	0	0	A56.2616-45G
	Dia.45mm, Yellow	0	0	A56.2616-45A
	Dia.45mm, Neutral	0	0	A56.2616-45N

C-Mount 0.5x, Focus Adjustable	0	0	A55.2601-05
C-Mount 0.75x, Focus Adjustable	0	0	A55.2601-75
C-Mount1.0x, Focus Adjustable	0	0	A55.2601-10
Digital Eyepiece Camera Adapter, Dia. 23.2mm/25mm	0	0	A55.2610
Carton Size 570×275×450mm, 1 Unit/Ctn			
Gross Weight: 8.6 kgs, Net Weight: 7.5 kgs			
, ,			
	C-Mount 0.75x, Focus Adjustable C-Mount1.0x, Focus Adjustable Digital Eyepiece Camera Adapter, Dia. 23.2mm/25mm Carton Size 570×275×450mm, 1 Unit/Ctn Gross Weight: 8.6 kgs, Net Weight: 7.5 kgs Table Is Standard outfits, "O" Is Optional	C-Mount 0.75x, Focus Adjustable  C-Mount1.0x, Focus Adjustable  Digital Eyepiece Camera Adapter, Dia. 23.2mm/25mm  Carton Size 570×275×450mm, 1 Unit/Ctn  Gross Weight: 8.6 kgs, Net Weight: 7.5 kgs  Table Is Standard outfits, "O" Is Optional	C-Mount 0.75x, Focus Adjustable  C-Mount1.0x, Focus Adjustable  Digital Eyepiece Camera Adapter, Dia. 23.2mm/25mm  Carton Size 570×275×450mm, 1 Unit/Ctn  Gross Weight: 8.6 kgs, Net Weight: 7.5 kgs  Table Is Standard outfits, "O" Is Optional

Product Display

Non-Stress Infinity Plan Objective 4x,10x,20x,40x Available, 60x, 100x(Optional)

Round Stage Diameter  $\Phi$ 142mm, Rotatable 360°, Division 1', Vernier Division 6', Can Be Locked, Center Adjustable. (Newly Updated in 2019)







Number	Specification	Cata. No.
01	C-Mount 0.5x, Focus Adjustable	A55.2601-05
02	C-Mount 0.75x, Focus Adjustable	A55.2601-75
03	C-Mount 1.0x, Focus Adjustable	A55.2601-10
04	Digital Eveniene Comera Adapter	A55 2610



## Opto-Edu (Beijing) Co., Ltd.







F-1501 Wanda Plaza, No. 18 Shijingshan Road, Beijing 100043, China