



Binocular Head Compound Metallurgical Optical Microscope A13.0209

Basic Information

Place of Origin: China

Brand Name: CNOEC, OPTO-EDU

Certification: CE, Rohs
Model Number: A13.0209
Minimum Order Quantity: 1 pc

Price: FOB \$1~1000, Depend on Order Quantity
 Packaging Details: Carton Packing, For Export Transportation

• Delivery Time: 5~20 Days

Payment Terms: T/T, West Union, Paypal

Supply Ability: 5000 pcs/ Month



Product Specification

Application: Research, Metallurgical

Certification: CE, RohsDrawtube: Binocular

Illumination: Halogen Lamp, LED

Magnification: 50X - 500X

• Theory: Metallurgical Optical Microscope

 Highlight: bright field microscope, halogen lamp microscope



Product Description

Binocular Compound Metallurgical Optical Microscope A13.0209

Description:

A13.0209 metallurgical microscope is used for identification and analysis of the structures in different metals and alloys, it is the important instrument for researching metallography in metal physics.

- --Plan achromatic objectives with long working distance (no cover glass)
- --Coaxial coarse/fine focusing system with tension adjustable and up stop
- --6V 20W halogen lamp with brightness control
- --Trinocular head can switch between normal observation and polarizing observation

Specifications:

Specification		A13.0209- A A13.0209-B			
Eyepiece		WF10X(Φ18mm)			
Objective		Plan long working distance (no cover glass) PL5x/0.12			
		Plan long working distance (no cover glass) PLL10x/0.25			
		Plan long working distance (no cover glass) PLL20x/0.40			
		Plan long working distance (no cover glass) PLL50x/0.7			
Head		Trinocular, inclination of 30°, analyzer with field diaphragm to switch			
Vertical illumination Unit		6V 20W halogen lamp with brightness control			
		Vertical illumination with field diaphragm, aperture diaphragm and polaizer, (YBG) filter and ground glass			
Transmited Illumination Unit		Abbe condenser N.A.=1.25, Rack & pinion adjustable			
			Blue filter and ground glass		
			Collector for illumination with halogen lamp (W diaphragm)	ith filed	
			6V 20W, halogen lamp, adjustable brightness		
Focus System			arse/fine focus system, with tensional adjustable	e and up stop	
		minimum division of fine focusing: 2um			
Nosepiece		Quadruple back ball bearing inner locating			
Stage Double layer mechanical, size 210x140mm, moving range 75x50				75x50mm	
		Ol	ptional Accessories	Item No.	
Eyepiece	Wide	field WF16	A51.0203-16A		
	Divdi	ing 10x, 0.1	A51.025-G10		
Objective	Plan	long workin	A5M.0212-40		
		Plan long working distance (no cover glass) PLL60x/0.75(Spring) A5M.0212-6			
		long workin	A5M.0212-80		
	Plan	Plan long working distance (no cover glass)			
	PLL1	PLL10x/0.85(Spring)			
	Plan achromatic (no cover glass) PL100x/1.25			A5M.0212-100	
Nosepiece	Quintuple backward ball bearing inner locating			A54.0203-2	
CCD Adapter	0.4x			A55.0202-1	
	0.5x			A55.0202-4	
	1x			A55.0202-2	
	0.5x with dividing 0.1mm/Div			A55.0202-3	
Photo Adapter	2.5x/4x change over photograph attachment with 10x viewing eypiece			A55.0201-1	
				A55.0201-2	
	MD adapter			A55.0201-3	
	PK adapter			A55.0201-4	
DC Adapter	Digital Camera Adapter for CANON(A610,A620,A630,A640)			A55.02024-01	





Opto-Edu (Beijing) Co., Ltd.





sale@optoedu.com © cnoec.com



F-1501 Wanda Plaza, No. 18 Shijingshan Road, Beijing 100043, China