# Opto-Edu (Beijing) Co., Ltd.

# University Student 500X Optical Microscope With Digital Camera Rohs A32.0601-230

#### **Basic Information**

Place of Origin: China

Brand Name: CNOEC, OPTO-EDU

Certification: CE, RohsModel Number: A32.0601-230

• Minimum Order Quantity: 1 pc

Price: FOB \$1~1000, Depend on Order Quantity
 Packaging Details: Carton Packing, For Export Transportation

• Delivery Time: 5~20 Days

Payment Terms: T/T, West Union, Paypal

• Supply Ability: 5000 pcs/ Month



# **Product Specification**

Applications: Student, School, Laboratory

Certification: CE, Rohs
Illumination: LED
Max Magnification: 1000X

Theory: Digital Optical Microscope
 Image Sensor: 1.3M Pixel 1/2" Color CMOS
 Highlight: digital usb microscope, portable digital microscope



# More Images





# **Product Description**

#### Student 1000X Optical Microscope With Digital Camera A32.0601-230

#### Description:

Digital Optical Microscope, equipped with a digital camera allowing observation of a sample via a computer. Microscopes can also be partly or wholly computer-controlled with various levels of automation. Digital microscopy allows greater analysis of a microscope image, for example measurements of distances and areas, store your micro image, share and show them to your friends easily!

#### Specifications:

Specifications:			
A32.0601-230 Digital Video Zoom Specification			
Zoom Body of Zoom			
Range	U.1 A-T.UA		
Zoom Ratio	1:6.5		
Total Magnification	4.7x-1000x		
Semi-plan Achromatic	0.3x, 0.5x, 0.75x, 1.5x and 2x (optional)		
Objective	0.5x, 0.5x, 0.75x, 1.5x and 2x (optional)		
High-Power Objective	Ex and 10x (optional)		
Lens	5x and 10x (optional)		
Image Sensor	1.3M pixel 1/2" color CMOS		
Pixel Size	5.2um x 5.2um		
Spectrum Response	400nm-1000nm		
Scanning Type	Progressive scanning		
Exposal Type	ERS		
Resolution	1280x1024		
Transmission Rate	16f/s@1280*1024, 30f/s@640*480, 30f/s@320*240		
White Balance	Automatic operation supported		
Exposal Control	Manual opertion supported		
Image Output	USB2.0, 480Mb/s		
Function	Image capture, video recording and measuring function		
Laser Pointer	Wave length: 650nm		
Working Temperature	0-50 degree		
Minimum System Requirement	Windows 2000, XP and Vista Operation System		
	PIII 800 CPU or above		
	256MB Memory or above		
	64MB video memory or above		
	USB2.0 interfaces		
	1024*768 resolution monitor or above		
76mm stage LED high track stand	76mm scope holder		
	Travel length: 500mm		
	Travel distance:253mm		
	Coaxial focus: 23mm/circle		
	Fine focus: 0.56mm/circle		
	XY travel range:2x2" (50x50mm), the top of XY Dimensions:		
	150x150mm, Accuracy: 0.005mm or above oer 5mm		
	LED transmitted lighting base size: 320x316x21mm		
	With a 95x5mm glass plate		
	Voltage input: AC 90-240V, 50/60Hz		
Optional Accessories			
	0.3x, Semi-Plan, Outer Dia.30mm, W.D.331mm	A52.0626-03	
Objectives	0.5x, Semi-Plan, Outer Dia.30mm, W.D.198mm	A52.0626-05	
	0.75x, Semi-Plan, Outer Dia.30mm,	A F.O. 00000 7F	
	W.D.131mm	A52.0626-75	
	1.5x, Semi-Plan, Outer Dia.30mm, W.D.63mm	A52.0626-15	
	2.0x, Semi-Plan, Outer Dia.30mm, W.D.46mm	A52.0626-20	
	5x Infinity corrected long working distance		
	objective	A52.0627-5	
	10x Infinity corrected long working distance	AE2 0627 10	
	objective	A52.0627-10	
Illumination Assessed	Iris Diaphragm	A56.0606	
Illumination Accessories	LED side light	A56.0607	
Tripod & Accessories	Tripod,Full Size, 3.5Kgs, with Panhead.	A50.0604-11	
	Tilt Ball Head	A50.0604-12	
	Super Mag Slider, Made of Magnesium Alloy	A50.0604-13	
	Extension Bar, Total Length 600mm	A50.0604-14	
	Laptop Tray	A50.0604-15	
	Tilt Ball Head Adapte	A50.0604-16	
Polarizing Microscope	Polarizer	A5P.0602	
	4.8V 2200mA/h, Nickel hydrogen battery	A50.0602	

Rechargeable Battery

Battery Charger, Input Voltage 100-240V 50/60Hz, Output Voltage 6.0-6.5V, Current 250-A50.0602-R 350mA











# Opto-Edu (Beijing) Co., Ltd.



0086 13911110627



