40X - 1600X Trinocular Fluorescence Microscope Compound Microscopes A16.0801

Basic Information

• Place of Origin: China

• Brand Name: CNOEC, OPTO-EDU

Certification: CE, Rohs
Model Number: A16.0801
Minimum Order Quantity: 1 pc

• Price: Negotiation

Packaging Details: Carton Packing, For Export Transportation

• Delivery Time: 5~20 Days

• Payment Terms: T/T, West Union, Paypal

• Supply Ability: 5000 pcs/ Month



Product Specification

 Highlight: epi-fluorescence microscope, epifluorescence microscope

Product Description

40X - 1600X Trinocular Fluorescence Microscope Compound Microscopes A16.0801

- --Infinity optical system
- --High eyepoint wide field eyepiece, diopter adjustable
- --Super large working stage 160x142mm to hold 2 slides, for easier comparison
- --100W HBO ultra hi-voltage spherical mercury lamp give enough illumination

A16.0801 Specification					
Total Magnification	40x-1600x			•	
Eyepiece	WF10x/18mm, diopter adjustable, high eyepoint	•	1	•	
	WF16x/14mm, diopter adjustable, high eyepoint	•	1	•	
Head	Compensation brinocular head, 30° inclined, 360° rotatable,		Ţ		
	interpupillary distance 55-75mm, infinity optical system	ľ	1		
	Compensation trinocular head, 30° inclined, 360° rotatable,		Ī,		
	interpupillary distance 55-75mm, infinity optical system	L	Ţ		
Nosepiece			ŀ		
Objective	Fluorescence free objective 4x,10x, 40x (Spring),100x (Spring, Oil)	•	ŀ	•	
Focusing	Coaxial coarse and fine focusing knob, with tension adjustable ring and rack stop. coarse focusing range 22mm, fine focusing graduation is 0.002mm	•	•	•	
Stage	Stage Large double layer mechanical stage, size 160x142mm, moving range 76x52mm, can hold 2 slides.		ļ	•	
Condenser	r Abbe condenser N.A.=1.25, with iris diaphragm, height adjustable		•	•	
Light Source	Kohler illumination, iris adjustable, halogen lamp 12V20W, brightness adjustable	•	•	•	
Power	Power 90-240V wide voltage		1	•	
Adapter	Simple CCD Adapter	Γ	1		
Fluorescence Kit					
Exciting System	B(Blue) exciting light filter system EX490 DM510 BA515	•	1	•	
	G(Green) exciting light filter system EX545 DM580 BA590	•	1	•	
	O(Ordinary) transmit light system	•	7	•	
Light Source	100W HBO ultra hi-voltage spherical mercury lamp	•	1	•	
Power Box	AC220V/60Hz, with fuse 250V/8A	•	1	•	
Protection Barrier	Barrier to resist the ultraviolet light		•	•	
Oil	Fluorescent free objectives	•	ŀ	•	

Optional Accessories		
Fluorescence Attachment	U filter system	A57.0805- 01
	V filter system	A57.0805- 02
	Assistant exciting light filter system EX450-490	A57.0806
Adapter	1/3" CCD adapter	A55.0803
	1/2" CCD adapter	A55.0802
	Digital camera adapter	A55.0809
Camera	CCD camera (0.47M pixel)	A59.0803
	Digital CCD camera (2M, 3.1M, 5M pixel)	A59.0805





Opto-Edu (Beijing) Co., Ltd.

0086 13911110627

sale@optoedu.com

cnoec.com

F-1501 Wanda Plaza, No. 18 Shijingshan Road, Beijing 100043, China